

Piranha PII-140 Hydraulic Steelworker



Piranha PII-88 Dual Operator Steelworker gives metal fabricators outstanding quality and innovative features. Every Piranha provides quality work, saving time in set up, adaptability and versatility through a wide range of tooling, and factory engineering support. The Piranha Single Operator range are capable of performing most applications. However, when two simultaneous operations are required (e.g. punching and notching) a dual operator steelworker fits the bill.

Features

Punch Station

The urethane strippers keep the material flat to ensure a better quality punch. The shorter stroke ensures faster productivity and with no adjustments required results in an efficient and easy to use production.

Shearing Station

The urethane hold-downs clamp and unclamp the material automatically with each stroke ensuring faster productivity. Unlike other conventional steelworkers the parts remain clamped during the entire shearing cycle to ensure a more accurate result. The complete clamping cycle promotes longer blade life making it much more cost effective.

Shearing Visibility

Much easier to line up a cut line to the shear blade as the operator has a direct line of sight.

Shear Blade

The low rake angle shear blade results in flatter parts being produced at a better quality. Piranha provide four shear edges on each blade to enhance cost efficiency and blade longevity.

Angle Shear

The floating upper blade seats in the centre of the angle eliminating distortion ensuring the cut piece does not deform.

Coper Notch

The low rake angle blade keeps the part flat and under control during notching process.

Bending Attachment

The open ended attachment allows the angle to bent easily.

Installing the Attachment

The dovetail slide makes the bending attachment easy to install.

Ease of Use

All attachments and stations are at the same height making it easier to use. No need to adjust the feed table height between stations.

Options

- Pipe/Tube Bending Attachment
- Channel Die Block
- Bending Attachments – Optional sizes range from 300 – 1120mm
- 28XX Punch Attachment
- Press Brake Tooling Holders
- Quick set Gauging Tables – Fast set-up for punching multiple holes. Includes plate & angle-gauging guide bars. With left and right hand extensions available in 1.5m and 3m lengths.
- Channel Shear
- Bar Bender – Up to 65mm depending on available tonnage with adjustable die for different radii.
- Mechanical Backgauges
- Electrical Backgauges
- 38mm Oversize Punch Attachment
- Roller Feed Tables

Technical Specification

MODEL	PII-140
Throat Depth mm	520
Open height mm	350
Closed height mm	200
Stroke length mm	177
Plate table size (D-W) mm	410 x 915
Punch hole size (material) kN	1245
Max hole size (material) mm	35 - 127
Plate shear mm	520 Long, 25 x 350; 20 x 450; 12 x 500
Angle shear mm	150 x 150 x 16
Bar shear round mm	12 - 50
Bar shear square mm	12 - 35
Copper kN	845
Notcher mm	100 x 150 x 10
Optional Bending attachment length mm	450; 600; 915; 1220
Punch end strokes mm/min	24 / 25
Work station height (approx) mm	1118
Fluid capacity ltr	151
Motor kW	14
Length mm	965
Width mm	3048
Height mm	2159
Weight kg	5541