

TECHNICAL SPECIFICATION

Almi AL100U Belt Driven Pipe Notching Machine



Stock Code: 17104

The renowned, lever operated, AL100U-01 can grind material from \emptyset 20 mm to \emptyset 76.1 mm. Its compound slide and carriage with rotatable clamp are easily adjustable allowing the machine to grind all pipe sections at any angle between 30° and 90°.

The ALMI AL100U-01 can be used to grind square, rectangular and round pipes with a range of wall thicknesses and is suitable for all customary types of materials.

ALMI's belt tensioning system makes tensioning the grinding belt even easier. The belt is tensioned using the hex key supplied with the machine. The grinding belt can be tensioned quickly and the grinding rollers can be changed in seconds.

All pipe grinders are equipped with a deburring table.

Features

- Cost effective notching solution.
- Accurate.
- $\circ~$ Saves welding and finishing time.
- $\circ~$ Notches aluminium, mild steel and stainless steel.
- Ideal for boat building, hand rails, specialised vehicle frames, food process industry etc, etc.
- $\circ~$ Superior finished end product resulting in satisfied customers.

Technical Specification

MODEL	AL100U
Capacity mm	20 - 76
Angle notch to 60°	YES
Belt speed m/sec	30
Belt mm	100 x 2000
Motor kW	3
Length mm	1450
Width mm	650
Height mm	1150
Weight kg	200