

TECHNICAL SPECIFICATION

Almi AL150 Belt Driven Pipe Notching Machine



Stock Code: 17105

The AL150 can be operated with two hand-wheels or a lever. The machine is equipped with both options. The AL150 can be used to grind material from \varnothing 20 mm to \varnothing 114.3 mm. The compound slide and carriage with rotatable clamp are easily adjustable, which means the machine can grind all pipe sections at any angle between 30° and 90°.

The ALMI AL150 can be used to grind square, rectangular and round pipes with a range of wall thicknesses and is suitable for all customary types of materials.

ALMI's belt tensioning system makes tensioning the grinding belt even easier. The belt is tensioned using the hex key supplied with the machine. The grinding belt can be tensioned quickly and the grinding rollers can be changed in seconds.

All pipe grinders are equipped with a deburring table.

Features

- o Cost effective notching solution.
- o Accurate.
- $\circ\,$ Saves welding and finishing time.
- o Notches aluminium, mild steel and stainless steel.
- Ideal for boat building, hand rails, specialised vehicle frames, food process industry etc, etc.
- $\circ\;$ Superior finished end product resulting in satisfied customers.

Technical Specification

MODEL	AL150
Capacity mm	20 - 114.3mm
Angle notch to 60°	YES
Belt speed m/sec	30
Belt mm	150 x 2000
Motor kW	4
Length mm	1450
Width mm	850
Height mm	1200
Weight kg	260