

## Sterling SRC 275 R Circular Saw



The heavy construction and quality finish of the Sterling SRC range of circular sawing machines is outstanding. Models with 275, 315 and 350mm diameter blades are offered as not only the standard pull down version – with or without a pneumatic vice system – but also in a fast cutting semi-automatic design for production cutting. Double clamping and self-centring vices ensure material is always securely clamped in the optimum cutting position.

Features

- Heavy duty construction
- High quality gearbox in oil bath
- Pull down operation
- Double head return springs
- Quick set mitring 45° left and right
- Pneumatic vice operation
- Double clamping anti-burr vice
- Self centring vice to ensure cutting is in optimum position
- 2 speed motor
- Electrical coolant pump
- Coolant resevoir in base with return filter
- Adjustable length stop bar

Options

- Roller track and measuring systems

Technical Specification

|                  |                |
|------------------|----------------|
| MODEL            | SRC 275 R      |
| Capacity         | 90°, 45°       |
| - Round mm       | 85, 70         |
| - Square mm      | 70, 60         |
| - Rectangular mm | 95x60, 70x55   |
| Blade Size mm    | 275ø x 32 bore |
| Blade Speed rpm  | 45/90          |
| Motor Kw         | 1.0 / 1.3      |
| Length mm        | 1100           |
| Width mm         | 600            |
| Height mm        | 1400           |
| Weight Kg        | 185            |
| Operation        | Pull Down      |
| Vice             | Manual         |