

TECHNICAL SPECIFICATION

Morgan Rushworth PB NC 3100/90 Hydraulic Pressbrake

Stock Code: M5004



The conventional PB series pressbrake are manufactured with a heavy duty welded steel frame with strong tortion bar and hydro mechanical balancing system ensuring a long working life. PB machines range from 35 tonnes through to 300 tonnes with a bending length of up to 4100mm. All PB machines accept euro style tooling and are supplied with digital readouts for stroke control and for the power backgauge position. Side and rear guards with electrical interlocks are fitted as standard for increased safety.





Features

- o European style top tool holders with wedge adjustment.
- o Standard tooling: Gooseneck top tool and multi-vee bottom
- o Front operated, 750mm ballscrew backgauge with digital readout control (to 0.1mm precision) and two finger-stops with micro-adjustable height.
- o Ram stroke control by precision mechanical-stops built into each cylinder and electrically adjusted by push-buttons with a digital position display.
- Independent position control of one cylinder-stop to provide fine angle adjustment and/or conical bending possibility.
- o Pressure switch and gauge to regulate bending tonnage and to prevent overbending due to bottoming of tools.
- o Pre-set, two-speed bending cycle giving fast approach, slow bending and fast return.
- o 3-function footswitch: normal bending, beam pause at any stroke point, automatic beam return upon release of footswitch.
- o Pendant control unit.
- o Hand screw clamps and chains to align and secure bottom die.
- o Two backgauge fingers.
- Two front support arms.

MODEL	PB NC 3100/90
Bending power tonnes	90
Bending length mm	3100
Distance between columns mm	2550
Y rapid speed mm/sec	95
Y working speed mm/sec	10
Y return speed mm/sec	80
Travel in X axis mm	750
Oil capacity Ltr	170
Motor power kW	7.5
Stroke mm	120
Daylight mm	460
Throat depth mm	310
Table height mm	870
Table width mm	140
Machine width mm	1300
Length mm	4350
Height mm	2270
Width mm	1650
Weight kg	6500

Technical Specification

Options

- o Programmable (NC) control for Y (stroke) and X (backgauge) axes.
- o 1000mm backgauge length.
- Top tool quick release clamps.
- o Laser tool guard.
- o Anti deflection system.
- o Additional backgauge fingers.
- o Additional front support arm.