


Morgan Rushworth PBS CNC 3100/200 Hydraulic Pressbrake

Stock Code: M5049



The new Morgan Rushworth PBS CNC hydraulic pressbrakes are fitted with the new ESA CNC controller to enable off line programming from PC. Multi bend operations with complex forms can thus be effectively managed reducing operator error and over or under bending. The Y1 and Y2 axis are fully synchronised and accurate to 0.01mm with proportional valve technology. Monoblock welded steel frame ensures minimum deflection under maximum load. The AKAS laser tool guards are now standard and ensure a vastly improved operator experience. A comprehensive range of options including anti deflection tables are available to fully 'tailor' the machine to customer requirements.



Features

- Strong rigid welded Monoblock frame able to withstand deflection under load.
- AKAS laser tooling guards.
- User friendly ESA CNC system with 2D auto bend sequence computations and large tool library.
- Full off line 2D graphical view programming software which can be transferred to the controller with USB flash disc.
- Ideal for multi bending of complex operations, especially where volume production with accurate repeatability is required.
- Bend accuracy at least five times higher than conventional pressbrakes.
- Fully synchronised Y1 and Y2 axis, accurate to 0.01mm with proportional valve technology.
- Hydraulic ram travel guided in low friction slideways.
- Fast CNC backgauge with AC servo drive.
- Euro style top clamps with intermediaries and quick release tool clamps.
- Sectionalised goose neck top tool.
- Sectionalised multi vee bottom die.
- High stroke and daylight opening.
- Deep throat design
- Two front support arms on adjustable linear rail
- Dual foot switch console with emergency stop.
- Swivelling pendant arm.
- Rear guard with photo cell safety beam.
- Ventilated electrical cabinet.

Options

- Manual anti deflection table
- CNC anti deflection table
- S560 2D colour graphical CNC touch screen controller
- Extra backgauge fingers

Technical Specification

MODEL	PBS CNC 3100/200
Bending power tonnes	200
Bending length mm	3100
Distance between columns mm	2550
Y rapid speed mm/sec	100
Y working speed mm/sec	7.7
Y return speed mm/sec	80
Travel in X axis mm	1000
Speed of X axis (Standard AC axes) mm/sec	350
Travel in R axis mm	160
Operational speed of dynamic Servo R axes mm/sec	240
No of backgauge finger blocks	2
No of sheet support arms	2
Oil capacity Ltr	210
Motor power kW	18.5
Stroke mm	260
Daylight mm	530
Throat depth mm	410
Table height mm	880
Table width mm	90
Machine width mm	1600
Length mm	4350
Height mm	2905
Weight kg	10000